

Temperature Compensated Crystal Oscillators [TCXO " M " and VCTCXO " VM "]

TCXO			VCTCXO			N series	SMD	2.5V	3.3V	Min.	Max.
MQN _ T	MQN _ P	MQN _ D	VMQN _ T	VMQN _ P	VMQN _ D					10 MHz	1,500 MHz
CMOS	PECL	LVDS	CMOS	PECL	LVDS						
Features						0.8 pS Phase Jitter (typical)					

- Wide frequency range : 10 ~ 1500 MHz
- RMS Jitter (12 kHz ~ 20MHz) : 0.8 ps typ. (at 156.250 MHz)
- Package size : 3.2 x 2.5 x 1.6mm and 7.0 x 5.0 x 2.5mm
- Single end output : CMOS , Differential output : LVPECL or LVDS



General specifications , at Ta=+25°C

Model	(V)MQN326T , (V)MQN574T		(V)MQN326P , (V)MQN576P			(V)MQN326D , (V)MQN576D		
Output Logic	CMOS		PECL			LVDS		
Supply Voltage V _{DD} (code)	+ 2.5 V _{DD} ± 5% (voltage code " 25 ")		+ 2.5 V _{DD} ± 5% (voltage code " 25 ")			+ 2.5 V _{DD} ± 5% (voltage code " 25 ")		
	+ 3.3 V _{DD} ± 5% (voltage code " 33 ")		+ 3.3 V _{DD} ± 5% (voltage code " 33 ")			+ 3.3 V _{DD} ± 5% (voltage code " 33 ")		
Available Frequency Range	10 ~ 250 MHz		10 ~ 1,500 MHz			10 ~ 1,500 MHz		
Output Load	15 pF		50 Ω into Vcc - 2V or Thevenin equivalent			100 Ω		
Output Logic " High " , " 1 "	90 % V _{DD}		V _{DD} - 1.03 (min.) , V _{DD} - 0.6 (max.)			1.4 V (typ.) , 1.6 V (max.)		
Output Logic " Low " , " 0 "	10 % V _{DD}		V _{DD} - 1.85 (min.) , V _{DD} - 1.6 (max.)			1.1 V (typ.) , 0.9 V (min.)		
(V _{DD} = + 2.5V)	50 MHz : 34 mA		156 MHz : 46 mA			156 MHz : 32 mA		
Current Consumption (max.)	125 MHz : 38 mA		600 MHz : 50 mA			800 MHz : 40 mA		
	200 MHz : 40 mA		1,000 MHz : 60 mA			1,000 MHz : 44 mA		
(V _{DD} = + 3.3V)	50 MHz : 36 mA		156 MHz : 50 mA			156 MHz : 35 mA		
Current Consumption (max.)	125 MHz : 40mA		600 MHz : 55 mA			800 MHz : 40 mA		
	200 MHz : 44 mA		1,000 MHz : 62 mA			1,000 MHz : 44 mA		
Current with Output Disabled	18 mA (typ.)		18 mA (typ.)			18 mA (typ.)		
Rise Time / Fall Time	1.5 nsec. (typ.) , 3.0 nsec. (max.) Tr / Tf : 10% ↔ 90% waveform		0.2 nsec. (typ.) , 0.5 nsec. (max.) Tr / Tf : 20% ↔ 80% waveform			0.2 nsec. (typ.) , 0.4 nsec. (max.) Tr / Tf : 20% ↔ 80% waveform		
Initial Calibration Tolerance	± 1.0 ppm. (max.) at +25°C±2°C. (upon shipment) for Package Size (3.2 * 2.5 mm)							
	± 2.0 ppm. (max.) at +25°C±2°C. (upon shipment) for Package Size (5.0 * 7.0 mm)							
Frequency Stability Codes	Temperature (ref to +25°C)	± 2.0 ppm over -40°C to +85°C (default)						
		± 1.0 ppm over -40°C to +85°C (available)						
	Aging at Ta = +25°C	± 1.0 ppm max . , per year at 25°C						
	Voltage Change	± 0.2 ppm max . , for a ±5% input voltage change.						
	Load Change	± 0.2 ppm max . , for a ±10% load condition change.						
	Reflow	± 1.0 ppm max . , 1 reflow and measured 24 hours afterwards.						
Duty Cycle	50 % ± 5%							
Start-up Time	5.0 msec. (max.)							
RMS Jitter [12 kHz ~ 20 MHz]	0.8 psec (typ.)							
Phase Noise [dBc / Hz (typ.)]	Offset	10 Hz	100 Hz	1K Hz	10K Hz	100K Hz	1M Hz	10M Hz
	125 MHz	-51	-93	-111	-123	-125	-135	-155
	212.5 MHz	-42	-87	-105	-115	-118	-130	-151
Storage Temperature	-55°C to + 125°C							
Control Voltage Function on Pad 1				Output Enable Function on pad 2				
Control Voltage Center and Range	+1.5V ± 1.0V for both V _{DD} = 2.5V and 3.3V			OE Control on Pad 2	70% of V _{DD} (min.) to enable output. (Open connection prohibit.)			
Frequency Pulling Range	± 8 ppm (min.)				30% of V _{DD} (max.) to disable output (high impedance).			
Linearity	1% (typ.) ; 10% (max.)							
Transfer Function	Positive Transfer							
Absolute Voltage	4.0 V (max.)			Ouput Enable Time / Disable Time	200 nsec. (max.) / 50 nsec. (max.)			
Input Impedance	770 KΩ (typ.)							

Temperature Compensated Crystal Oscillators [TCXO " M " and VCTCXO " VM "]

TCXO			VCTCXO			N series	SMD	2.5 V 3.3 V		Min.	Max.
MQN _ T	MQN _ P	MQN _ D	VMQN _ T	VMQN _ P	VMQN _ D					10 MHz	1,500 MHz
CMOS	PECL	LVDS	CMOS	PECL	LVDS						

Part Number Format and Example

	[1]	[2]	[3]	[4]	-	[5]	-	[6]	/	[7]
	Holder Type	Package Code	Waveform Code	Supply Voltage		Center Frequency		Frequency Stability		Operating Temp. Range
Examples	(1) MQN	326	D	25	-	622.080	-	1.0	/	-40+85
	(2) VMQN	576	P	33	-	120.000	-	2.0	/	-40+85

Ex (1) : MQN326D25 - 622.080 - 1.0 / -40+85 [TCXO , MQN326 type , LVDS , +2.5V , 622.080MHz , ±1.0ppm from -40°C to 85°C]

Ex (2) : VMQN576P33 - 120.000 - 2.0 / -40+85 [VCTCXO , VMQN576 type , PECL , +3.3V , 120.000MHz , ±2.0ppm from -40°C to 85°C]

[1]	Holder Type : " MQN " stands for TCXO ; " VMQN " stands for VCTCXO
[2]	Package Code : " 326 " stands for 3.2 x 2.5 x 1.6 mm 6pad ; " 576 " stands for 5.0 x 7.0 x 2.5 mm 6pad
[3]	Output Waveform Code : " T " stands for CMOS ; " P " stands for PECL ; " D " stands for LVDS
[4]	Supply Voltage : " 25 " stands for +2.5V ; " 33 " stands for +3.3V
[5]	Center Frequency in MHz
[6]	Frequency Stability in ± ppm ; ex 1 : ± 1.0ppm --- 1.0 , ex 2 : ± 2.0ppm --- 2.0
[7]	Operating Temperature Range in °C ex : -40 °C to 85°C ----- -40+85

Outline Dimensions (Unit : mm) , Suggested pad Layout for SMDs

[(V)MQN574T]	[(V)MQN576P] , [(V)MQN576D]	[(V)MQN326T] , [(V)MQN326P] , [(V)MQN326D]
 Pad Connections : Pad 1 : NC for TCXO ; VC for VCTCXO Pad 2 : Ground Pad 3 : Output Pad 4 : Supply Voltage	 Pad Connections : Pad 1 : NC for TCXO ; VC for VCTCXO Pad 2 : Output Enable Pad 3 : Ground Pad 4 : Output Pad 5 : Complementary Pad 6 : Supply Voltage	 Pad Connections : Pad 1 : NC for TCXO ; VC for VCTCXO Pad 2 : Output Enable Pad 3 : Ground Pad 4 : CMOS : Output ; PECL / LVDS : Differential Pad 5 : CMOS : No Connection ; PECL / LVDS : Complementary Pad 6 : Supply Voltage


Test Circuits and Output Waveforms

CMOS for 4pad package	CMOS for 6pad package
PECL	LVDS
$V_{DD} = 3.3V$: $R1 = R3 = 127\Omega$; $R2 = R4 = 82.5\Omega$ $V_{DD} = 2.5V$: $R1 = R3 = 250\Omega$; $R2 = R4 = 62.5\Omega$	

Emboss Taping and Reel Specifications

[VCXO]

[(VC)TCXO]



Carrier Type Dimensions (unit : mm) ±0.3mm

	A	B	C	D	E	F	G	H	I	pcs / reel
G_226	8.00	2.80	2.25	4.00	1.10	0.30	4.00	Ø 1.50	1.75	3000
G_326	8.00	3.40	2.70	4.00	1.40	0.25	4.00	Ø 1.50	1.75	3000
G_536	12.00	5.30	3.60	8.00	1.40	0.30	4.00	Ø 1.50	1.75	1000
G_576	16.00	7.30	5.30	8.00	1.90	0.30	4.00	Ø 1.50	1.75	1000
G_538	12.00	5.40	3.60	8.00	1.70	0.30	4.00	Ø 1.50	1.75	1000
G_578	16.00	7.30	5.30	8.00	1.90	0.30	4.00	Ø 1.50	1.75	1000
(V)M21	8.00	2.30	1.90	4.00	0.90	0.25	4.00	Ø 1.50	1.75	3000
ME21	8.00	2.30	1.50	4.00	1.35	0.25	4.00	Ø 1.50	1.75	3000
(V)M22	8.00	2.80	2.25	4.00	1.10	0.30	4.00	Ø 1.50	1.75	3000
(V)M_32	8.00	3.71	2.80	4.00	1.75	0.25	4.00	Ø 1.50	1.75	3000
(V)M_326	12.00	3.60	2.90	4.00	1.70	0.30	4.00	Ø 1.50	1.75	1000
(V)M_53	12.00	5.30	3.60	8.00	1.40	0.30	4.00	Ø 1.50	1.75	1000
(V)M_538	12.00	5.40	3.60	8.00	1.70	0.30	4.00	Ø 1.50	1.75	1000
(V)M_57(2)	16.00	7.40	5.50	8.00	2.80	0.35	4.00	Ø 1.50	1.75	500
(V)M_43 (63)	24.00	11.80	10.00	16.00	5.00	0.30	4.00	Ø 1.50	1.75	500

Reel Dimensions (unit : mm) +2.0 / -0.0mm

	J	K	L	P	Q	R	pcs / reel
G_226	180.00	9.00	12.00	13.20	2.10	-	3000
G_326	180.00	9.00	12.00	13.20	2.10	-	3000
G_536	180.00	13.00	16.00	13.20	2.50	-	1000
G_576	180.00	17.20	19.30	13.30	2.20	22.00	1000
G_538	180.00	13.00	16.00	13.20	2.50	-	1000
G_578	180.00	17.20	19.30	13.30	2.20	22.00	1000
(V)M21	180.00	9.00	12.00	13.20	2.10	-	3000
ME21	180.00	9.00	12.00	13.20	2.10	-	3000
(V)M22	180.00	9.00	12.00	13.20	2.10	-	3000
(V)M_32	180.00	9.00	12.00	13.20	2.10	-	3000
(V)M_326	180.00	13.00	16.00	13.20	2.50	-	1000
(V)M_53	180.00	13.00	16.00	13.20	2.50	-	1000
(V)M_538	180.00	13.00	16.00	13.20	2.50	-	1000
(V)M_57(2)	180.00	17.20	19.30	13.30	2.20	22.00	500
(V)M_43 (63)	330.00	24.50	29.10	13.00	2.20	17.30	500